




12" x 18" Gable Vent Model # GV2021-FF



Gable Vents	Model	Size W x L	NFVA Provided (Sq In)	Flanges Available	Flange Definition	Weight
	GV2021-FF	12" x 18"	60.9	Flange Front	Flange Front	6lbs
Custom sizes/shapes/materials AVAILABLE						

BENEFITS:

- Safety vents that are used in areas prone to wildfires, wind driven rain, or winddriven snow.
- **Triple Protection (Patented)**
 - Overlapping baffles resist embers, flames and radiant heat
 - Heat activated Intumescent Strips expand & seal openings during extreme fire conditions
 - 1/16" mesh on back side of vent for additional ember and bug protection
- WUI Approved for use throughout California and beyond (Calfire BML Approval # 8165-2232:0502)
- Tested and Listed to ASTM E2886/2912
- 1 hour Fire Rated per ASTM E119
- Tested to Miami Dade County Driving Rain up to 140mph with no rain intrusion
- Air Flows through normally
- Also Prevents Rodent Entry
- Easy to Install, Retrofit and Paint

STANDARD MATERIALS

ASTM A653/A653M- G90 hot dipped galvanized steel, 26GA ASTM D9092- mill phosphatized coating for painting. IF BONDERIZED ASTM b370- Sheet Copper, 16oz and 20oz IF GALVANIZED .0625 x.0625 hot dipped galvanized 23ga wire mesh

Installation:

Install like any other similar Ventilator Product on the market.