



### Key Features

- Great for contractors building custom systems
- Flexible wall-mounting coils
- Quiet and efficient in-cellar operation
- 55°F temperature differential
- Sleek black powder-coated finish
- Bottle probe measures liquid temperature
- Built-in control

### Specifications

Model	WM2500-CR	WM3500-CR	WM5000-CR
Cellar Size (cu. ft.)	500	1000	2000
BTU/h (w/85°F air entering the condenser coil)	2101	3650	5211
CFM	99	270	
Dimensions	20"W x 10.5"H x 13"D	20.5"W x 15.5"H x 16.1"D	
Refrigerant	R-134a		
Condensing Unit HP	1/6	1/3	
Voltage Rating	110V (20 amp dedicated circuit required)		
Weight (lbs)	25	56	
Amps (LRA/RLA)	2/1	2/1	
dBA (Evaporator)	51	54	
Line Set	Please refer to the technician's manual		
Drain Line	1/2" ID clear plastic tubing (not provided)		
Installation	Evaporator coil installed in the cellar		
Thermostat	Digital display with bottle probe		
Temp. Delta	55°F temperature differential between cellar environment and condensing unit intake air		
Suggested Condenser	Copeland: M7JH-0014	Copeland: M7EH-H041	Copeland: M7EH-H046
Warranty	Two-year limited warranty (parts and labor)		

CR units come with the Evaporator, Controller & Bottle Probe. The Condenser is supplied and warranty by others. The condenser size must be matched with the proper size CellarCool Evaporator for the system to work properly. The wrong match will void the warranty.