



Key Features

- Ready for “plug-and-play” installation
- Flexible wall-mounting coils
- Quiet and efficient in-cellar operation
- 55°F temperature differential
- Advanced electronic control system
- Bottle probe measures liquid temperature
- Built-in control
- Built-in cold weather start kit on condensing unit

Specifications

Model	WM2500-S	WM3500-S	WM5000-S
Cellar Size (cu. ft.)	500	1000	2000
BTU/h (w/85°F air entering the condenser coil)	2101	3650	5211
CFM	99	270	
Dimensions	Evaporator: 10.5”H x 20”W x 13”D Condenser: 9.86”H x 15.85”W x 13.967”D	Evaporator: 15.5”H x 20.5”W x 16.1”D Condenser: 11.9”H x 15.1”W x 16.1”D	
Refrigerant	R-134a		
HP	1/6	1/3	
Voltage Rating	110V (20 amp dedicated circuit required)		
Weight (lbs)	Evaporator: 25, Condenser: 38.8	Evaporator: 56, Condenser: 55	
Amps (LRA/RLA)	Evaporator: 2/1, Condenser: 26/4.4	Evaporator: 2/1, Condenser: 48.7/8	Evaporator: 2/1, Condenser: 50/9.3
dBA (Evaporator/Condenser)	51/65	54/65	
Line Set	Please refer to the technician’s manual		
Drain Line	1/2” ID clear plastic tubing (not provided)		
Installation	Evaporator unit is installed in the cellar. Condensing unit is installed up to 100 feet from evaporator unit. Allow for adequate airflow.		
Thermostat	Digital display with 50-ft. cable and 50-ft. bottle probe		
Temp. Delta	55°F temperature differential between cellar environment and condensing unit intake air		
Warranty	Two-year limited warranty (parts and labor). Technician MUST return charging records to CellarCool to validate warranty.		

* New factory installed Cold Weather Start (-15 F) included.

Optional Accessories

Exterior condenser housing