



Horizontal Portable Products

Air-Cooled



**Cooling Only or Cooling/Heating
Available with Optional Dehumidification Mode**

- **Narrow Portable 3–5 Ton** —
-5 Ton Heat Pump
 - Only 29.5" wide- fits through standard 36" doors
 - Available as cooling only, cooling with electric heat, heat pump or heat pump with auxiliary electric heat configuration
- **Narrow Portable 12 Ton** —
 - Only 34.5" wide - fits through standard 36" doors
 - Available as cooling or cooling with electric heat
 - Integral fork lifting pod and 8" casters
- **20–30 Ton Cooling** —
-Up to 60 kW Heating
-Base, Pod or DOT approved Trailer Mounted
 - Tubular frame construction
 - Low profile design
 - Ideal for temporary cooling or heating in renovation projects, spot cooling or heating, temporary cooling when the building air conditioner is down or when extra cooling or heating is needed to supplement the building system

All units utilize scroll design compressors.





Horizontal Portable Air Conditioning Products

Physical Data						
	Model Number	Tons	Dimensions (W x H x L)	Approx. Weight	Voltage/Phase	MCA
Cooling/Heating	HKW3N	3	29.50 x 54.50 x 67.00	590	208/1 208/3	38.9 25.3
	HKW5N	5	29.50 x 54.50 x 67.00	690	208/1 208/3	55.6 36.6
	HKW12M	12	34.50 x 71.00 x 78.00	1500	208/3 460/3	59.6 30.4
	HKW20	20	95.50 x 57.00 x 95.50	2780	208/3 460/3	130.1 52.0
	HKW25	25	95.50 x 57.00 x 95.50	3000	208/3 460/3	162.4 67.5
	HKW30	30	95.50 x 67.00 x 95.50	3220	208/3 460/3	180.8 86.1
Heat Pump	HPKW5N	5	29.50 x 48.50 x 67.00	705	208/1 208/3 460/3	55.6 36.6 17.2

Note: KWH20–30 ton units also available mounted on DOT approved trailer assembly.

Standard Features	Options
<ul style="list-style-type: none"> • Unit Capacities: 3, 5, 10, 12, 20, 25 and 30 tons • Duct Collars • Evaporator Stainless Steel Drain Pan • R-410a Refrigerant • Terminal Block Power Connection • Phase Reversal Indicator Light • Durable White Powder Coat Finish • Condenser Coil Guard • Threaded Condensate Drain Connection • Main Circuit Breaker • Pleated Filters • Mode Switch • 4-Way Lifting Pod 	<ul style="list-style-type: none"> • Camlock Power-In Connectors • Available Voltages: 208/230-1-60 (3 thru 5 ton) 208/230-3-60, 460-3-60, 575-3-60 • Ductable Condenser Discharge • Hour Meter • Casters, Swivel/Lockable • Quarter Turn Access Panel Fasteners • Remote Thermostat w/ Cable • Trailer Mounted • Electric Heat 10kW-60kW • Phase Reversal Indicator • Duct Collar Covers

Note: Products can be configured with select features and a wider variety of options than what are listed here. Please contact Koldwave to discuss special features, paint colors, capabilities and configurations.



260 North Elm St.
Westfield, MA 01085
Phone: 413-564-5520
Fax: 413-564-5530

 A MESTEK COMPANY

SPÚŽ