



# Portable Heating Products

15-150 kW Heating



## Horizontal Heating/InLine Heaters and Blowers

- **Small Horizontal Heaters** — -15 kW to 60kW
  - Mounted on casters (swivel/lockable) for ease of mobility
  - Grab handles
  - The cabinet size permits easy access through most doorways to get the unit where it is needed
  - Typically the units are ducted, but can be provided with an optional free-blow bi-directional grille
- **Large Horizontal Heaters** — 150 kW
  - Mounted on a 4-way integral lifting pod
  - Up to four stages of heat provide for the heat output to match the load requirements
  - Use high static blowers to move the heated air through the flexible ducts to the space being heated
  - Heavy duty welded cabinet can be stacked for storage to save valuable floor space
- **InLine Blower** — -5,000 CFM
  - Horizontal cabinet
  - Mounted on casters
  - 4-way pod provides for use of a forklift from all sides
  - Unit designed for ducted applications (20") with up to 5" External Static Pressure (ESP)

Physical Data						
	Model Number	kW	Dimensions (W x H x L)	Approx. Weight	Voltage/Phase	MCA
Horizontal/ Heating	KWHH15	15	34.00 x 46.50 x 55.00	445	208/3 460/3	62.5 28.5
	KWHH30	30	34.00 x 46.50 x 55.00	460	208/3 460/3	114.6 52.1
	KWHH45	45	34.00 x 46.50 x 55.00	480	208/3 460/3	166.6 75.6
	KWHH60	60	34.00 x 46.50 x 55.00	495	208/3 460/3	258.9 117.3
	KWHH150	150	48.00 x 52.75 x 76.00	1290	460/3	258.5
Horizontal Inline Blower	KWIB5 5000 CFM	N/A	38.00 x 51.50 x 52.00	582	208/3 460/3	33.2 14.4

**Note: To convert kW value, multiply by 3,412 to equal BTUH**

Standard Features	Options
<ul style="list-style-type: none"> <li>• Unit Capacities: 15, 30, 45, 60, 100 and 150 kW</li> <li>• Duct Collars</li> <li>• Durable Finned Tubular Heating Elements</li> <li>• Terminal Block Power Connection</li> <li>• Power Indicator Light</li> <li>• White Powder Coat Finish</li> <li>• Casters (Swivel/Lockable)</li> <li>• Main Circuit Breaker</li> <li>• Cleanable Filters</li> <li>• Mode Switch</li> <li>• Unit Mounted Thermostat</li> </ul>	<ul style="list-style-type: none"> <li>• Hour Meter</li> <li>• Camlock In Power Connections</li> <li>• Quarter Turn Fasteners on Access Panels</li> <li>• Insulated Inlet Air Section</li> <li>• Fork Lift Pockets</li> </ul>

**Note:**

Products can be configured with select features and a wider variety of options than what are listed here. Please contact Koldwave to discuss special features, paint colors, capabilities and configurations.



260 North Elm St.  
Westfield, MA 01085  
Phone: 413-564-5520  
Fax: 413-564-5530