








Model Selection






Indoor Use Models	Effectiveness @ 0° C (32° F)	Dimensions H x W x D (in)	Product Features
 <p>350 DCS 350 DCS-REV</p>	95%	18.750 (H) 49.000 (W) 28.250 (D)	Airflow up to 400 CFM*; Highly efficient dual core system features a low profile cabinet designed for installations above suspended ceilings. Digital wall control included.
 <p>455 FD 455 DD</p>	65%	25.625 (H) 29.625 (W) 28.750 (D)	Airflows up to 450 CFM*; Compact and reliable unit for installation in tight locations. Available in damper defrost (DD) or fan defrost (FD).
 <p>650 FD 650 DD</p>	80%	24.625 (H) 46.750 (W) 41.500 (D)	Airflow up to 650 CFM*; Two sets of cores in series allows for high efficiency transfer of energy between airstreams. Low profile cabinet allows for installations above suspended ceilings. Available in fan defrost (FD) or damper defrost (DD).

NEW RELEASES







 <p>700 FD 700 DD</p>	65%	32.25 (H) 33.25 (W) 29.00 (D)	Airflow up to 700 CFM*; Compact and reliable unit for installation in tight locations. Access door located on front and back, blowers slide easily in/out for service and maintenance. Field reversible. Available in fan defrost (FD) or damper defrost (DD) and option to add MERV 8 filter (99-65-183).
 <p>1200 FD 1200 DD</p>	60%	32.25 (H) 33.25 (W) 42.00 (D)	Airflows up to 1200 CFM*; Compact and reliable unit for installation in tight locations. Access door located on front and back, blowers slide easily in/out for service and maintenance. Field reversible. Available in fan defrost (FD) or damper defrost (DD) and option to add MERV 8 filter (99-64-184).
 <p>700 POOL</p>	65%	32.25 (H) 33.25 (W) 29.00 (D)	Airflow up to 700 CFM*; Designed for indoor pool applications this compact unit delivers installation and operating costs to be less than alternative dehumidification systems. Access door located on front and back, blowers slide easily in/out for service and maintenance. Field reversible. Option to add MERV 8 filter (99-65-183). Includes remote dehumidistat.
 <p>1200 POOL</p>	60%	32.25 (H) 33.25 (W) 42.00 (D)	Airflow up to 1200 CFM*; Designed for indoor pool applications this compact unit delivers installation and operating costs to be less than alternative dehumidification systems. Access door located on front and back, blowers slide easily in/out for service and maintenance. Field reversible. Option to add MERV 8 filter (99-65-184). Includes remote dehumidistat.

*Refer to model specifications for design information. Specifications are available at www.lifebreath.com

Interior Models

Models	Effectiveness @ 0° C (32° F)	Dimensions H x W x D (in)	Product Features
 1500I-ECM	65%	37 x 66.75 x 44	Airflows up to 1500 CFM*; This high efficient, 3 speed unit features brushless DC motors producing quiet, long lasting operation while reducing energy costs. Standard fan defrost and various duct configurations available.
 2000 IFD-240SP	65%	39 x 66.75 x 57.25	Airflows up to 2500 CFM*; Fan defrost, 240 volt, single phase, single speed unit designed for interior installations. Various duct configuration options available.
 2000 IFD-460	65%	39 x 66.75 x 57.25	Airflows up to 2500 CFM*; Fan defrost, 460 volt, 3 phase, single speed unit designed for interior installations. Various duct configuration options available.
 2000 IFD-575	65%	39 x 66.75 x 57.25	Airflows up to 2500 CFM*; Fan defrost, 575 volt, 3 phase, single speed unit designed for interior installations. Various duct configuration options available.
 2500 IFD	70%	47 x 89.9 x 38.4	Airflows up to 2600 CFM*; 3 speed fan defrost unit designed for interior installations. Various duct configuration available.

Exterior Models

 1500E-ECM	65%	41 x 69.5 x 46.5	Airflows up to 1500 CFM*; This high efficient, 3 speed unit features brushless DC motors producing quiet, long lasting operation while reducing energy costs. Standard fan defrost and various duct configurations available.
 1500E-ECM-E	65%	41 x 69.5 x 46.5	Airflows up to 1500 CFM*; This high efficient, 3 speed unit features brushless DC motors producing quiet, long lasting operation while reducing energy costs. Standard fan defrost, side ported roof top unit with hoods. Various duct configurations available.
 2000 EFD-240	65%	43 x 69.5 x 59.75	Airflows up to 2500 CFM*; Fan defrost, 240 volt, single phase, single speed unit designed for exterior installations. Various duct configuration options available.
 2000 EFD-460	65%	43 x 69.5 x 59.75	Airflows up to 2500 CFM*; Fan defrost, 460 volt, 3 phase, single speed unit designed for exterior installations. Various duct configuration options available.
 2000 EFD-575	65%	43 x 69.5 x 59.75	Airflows up to 2500 CFM*; Fan defrost, 575 volt, 3 phase, single speed unit designed for exterior installations. Various duct configuration options available.
 2500 EFD	70%	47 x 89.9 x 38.4	Airflows up to 2600 CFM*; 3 speed fan defrost unit designed for exterior installations. Various duct configuration available.

*Refer to model specifications for design information. Specifications are available at www.lifebreath.com